

**Advanced TLP/HMM/HBM Solutions** 

## **Features**

- 20 dB surge robust attenuator for TLP, HMM and reverse recovery measurements
- DC 7 GHz bandwidth
- 2 kV peak pulse voltage
- SMA connectors (optional: N)

### **Description** 2

The attenuator HVA-20A is used to attenuate high voltage pulse signals in a 50  $\Omega$  line. The device is symmetrical. Input and output can be exchanged.

#### **Electrical Data** 3




Figure 1: Typical frequency response




Figure 2: Typical return loss



Nominal impedance	:	50	Ω
Nominal attenuation	:	$20^{+1}$	dB
Frequency range 1)	:	DC to 7	GHz
Peak pulse voltage <sup>2)</sup>	:	2	kV
Peak pulse power <sup>2)</sup>	:	80	kW
Maximum DC input voltage	:	22	V
Maximum DC input current	:	445	mΑ

<sup>1) +3</sup> dB

## **Physical Dimensions**




Figure 3: Dimensions (SMA version) in [mm]

# **Ordering Information**

Optional available with N-connectors (f/m). Please specify at order.

Pos.	Description	Part No.
01	High Voltage Attenuator 20 dB	HVA-20A

### General

The product data contained in this data-sheet is exclusively intended for technically trained staff. You and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application. Our products are solely intended to be commercially used internally and should not be sold to consumers. This data-sheet is describing the specifications of our products for which a warranty is being granted by HPPI GmbH. Any such warranty is granted exclusively pursuant the terms and conditions of the respective supply agreement. There will be no guarantee of any kind for the product and its specifications. For further information on technology, specific applications of our product, delivery terms, conditions and prices please contact HPPI:

High Power Pulse Instruments GmbH Stadlerstrasse 6A

D-85540 Haar, Germany Phone : +49 (0)89 8780698 - 440 Fax +49 (0)89 8780698 - 444 E-Mail info@hppi.de

Due to technical requirements our products and/or their application may be harmful. For information please read carefully the manual or contact HPPI. Safety notes in the manual will inform you about possible risks that result from any  $for esee able\ application\ of\ our\ products.\ Changes\ of\ this\ data-sheet\ are\ reserved.$ 

<sup>&</sup>lt;sup>2)</sup> max. 1 µs pulse width, max. 0.25 % duty cycle