

**Advanced TLP/HMM/HBM Solutions** 

## 1 Features

- 34 dB surge robust attenuator for TLP and HMM measurements
- Voltage attenuation factor k = 1/50
- 2 kV pulse peak input voltage at maximum 0.5 μs pulse width
- · SMA interface

## 2 Description

The attenuator HVA-34B is used to attenuate high voltage pulse signals in a  $50\,\Omega$  line. The device is not symmetrical. Input and output must not be exchanged. High voltage only at the input - otherwise the attenuator will damage.




Figure 1: Typical frequency response




Figure 2: Typical reflection coefficients



Nominal impedance	:	50	Ω
Nominal attenuation	:	34 -1	dB
Frequency range 1)	:	DC to 4	GHz
Attenuation deviation	:	< 2	dB
Maximum peak pulse input voltage <sup>2)</sup>	:	2	k۷
1) . 1 . 10			

<sup>&</sup>lt;sup>2)</sup> max. 0.5 μs pulse width, max. 0.25 % duty cycle




Figure 3: Dimensions in [mm]

## 3 Ordering Information

Pos.	Description	Part No.
01	High Voltage Attenuator 34 dB	HVA-34B

## General

The product data contained in this data-sheet is exclusively intended for technically trained staff. You and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application. Our products are solely intended to be commercially used internally and should not be sold to consumers. This data-sheet is describing the specifications of our products for which a warranty is being granted by HPPI GmbH. Any such warranty is granted exclusively pursuant the terms and conditions of the respective supply agreement. There will be no guarantee of any kind for the product and its specifications. For further information on technology, specific applications of our product, delivery terms, conditions and prices please contact HPPI:

High Power Pulse Instruments GmbH Stadlerstrasse 6A

D-85540 Haar, Germany
Phone : +49 (0)89 8780698 - 440
Fax : +49 (0)89 8780698 - 444
E-Mail : info@hppi.de

Due to technical requirements our products and/or their application may be harmful. For information please read carefully the manual or contact HPPI. Safety notes in the manual will inform you about possible risks that result from any foreseeable application of our products. Changes of this data-sheet are reserved.